

**TCXO & VCTCXO SMD2520 (CMOS Level Output)****4 Pad Version 2.5×2.0 mm**

- $\pm 0.5 \sim \pm 2.5$ ppm stability
- CMOS Level Output
- Low power consumption
- Reflow soldering temperature: 260°C max


RoHS
2002/95/EC

RoHS compliant

★ PARAMETERS

PARAMETERS	SPECIFICATION			
Frequency Range	10.0~60.0MHz			
Frequency Tolerance	±1.0ppm、±2.0ppm at +25± 2℃			
Frequency Stability	Vs Temperature (ref. to +25℃)		±0.5~ ±2.5ppm	
	Vs Supply voltage change (±5%)		±0.3ppm	
	Vs Load change (±10%)		±0.3ppm	
	Vs Aging (1 st Year , 25±2℃)		±1.0ppm	
Supply Voltage	1.8V、2.5V、2.8V、3.0V、3.3V			
Output Waveform	Square Wave			
Output Load	CMOS 15pF			
Current Consumption	6.0 mA max.			
Pad "1" Function	E/D			
Output Level	Logic High "1": 90% V _{DD} min.			
	Logic High "0": 10% V _{DD} max.			
Operating Temp. Range	-30~+85℃、-40~+85℃			
Storage Temp. Range	-55~+125℃			
Electrical Frequency Tuning (For VCTCXO)	Control Voltage Center	1.8V	2.5V/2.8V	3.0/3.3V
		0.9±0.6V	1.4±1.0V	1.5±1.0V
	Frequency Control Range	±5.0ppm min.		
Start-up Time	2.0mS typ., 5.0mS max.			
Phase Noise	-122 dBc/Hz max @100Hz offset			
	-138 dBc/Hz max @1KHz offset			
	-145 dBc/Hz max @10KHz offset			



⊙ All specification subject change without notice.

★ DIMENSIONS& LAND PATTERN LAYOUT (Unit: mm)

Pin	Connection
1	E/D (TCXO) V_{CON} (VCTCXO)
2	GND
3	Output
4	V_{DD}

**★ PART NUMBER GUIDE** e.g. FTO26.000M3.0SM2T1-1.0/2.5C (*SM2T1=2.5×2.0 SMD TYPE, CMOS, 1# E/D)

Logo	Type	Frequency	Supply Voltage	Package	Output Waveform	Frequency Tolerance	Frequency Stability	Operating Temp.
F	TO	26.000M	3.0	SM2	T1	1.0	2.5	C
	VTO				T			

★ TEST CIRCUIT**★ TAPING SPECIFICATION (Unit: mm)**

	A	B	C	D	E	F	G
TCXO-SMD2520	180±2.0	8.0±0.3	2.80±0.10	2.30±0.10	4.0±0.1	1.6±0.2	60.5±1.0
3000 pcs per reel							